


Sit.Net

Technical description

NowyStyl

1. Dimensions/Weight


SIT.NET ES


Model	Wymiary (mm)														Waga (kg)
	A	B	C	D	E	F	G	H	J	K	L	I	M	N	
SIT.NET-LU-HRUA TS25 RTS ES ESH	410–530	420	450	480	1020–1155	460	600	590	710	—	644	—	—	—	15
SIT.NET-LU-HRUA TS25 RTS EST ESH	420–540	420–480	450	480	1020–1155	460	600	590	710	—	644	—	—	—	16,2

A – Seat height
B – Seat depth
C – Seat surface depth
D – Seat width
E – Overall height

F – Backrest width
G – Backrest length
H – Backrest height
J – Base diameter
K – Base width

L – Overall depth
I – Headrest height
M – Headrest width
N – Headrest height




Armrests	Wymiary podłokietnika (mm)					Waga (kg)
	Z	Y	X	W	V	
R19I	200–280	255	90	480	660	1,8 (kpl)
R15K	200–280	255	90	455–510	635–690	3 (kpl)

Z – Armrest height
Y – Armrest length

X – Armrest width
W – Internal width between armrests

V – External width between armrests


SIT.NET CFP

	Wymiary (mm)												Waga (kg)
	A	A1	B	C	D	E	F	G	H	K	V	L	
SIT.NET CFP	465	430	455	450	490	1030	475	600	690	605	630	655	13,5

A – Seat height
A1 – Seat height according to standard EN 16139
B – Seat depth

C – Seat surface depth
D – Seat width
E – Overall height
F – Backrest width

G – Backrest length
H – Armrests height
L – Overall depth
V – Overall width

2. Materials/Versions

2.1. Base/Frame

2.1.1. Office swivel chairs

Bases:

- Ø 710 mm five-star black polyamide (TS25),
- Ø 700 mm five-star polished aluminium with chrome effect (ST44-POL).

Black gas lift without cover.

2.1.2. Conference frame chairs

Cantilever frame – made of chromium plated steel tube Ø 25 × 2.5 mm.

2.2. Castors/Glides

2.2.1 Office swivel chairs

Ø 65 mm black plastic self-braking castors for soft floors (ESH) as standard, or hard floors (ESHH) as an option.

2.2.2. Conference frame chairs

Glides for soft floors (GB) as standard, or hard floors (GBF) as an option.

2.3. Mechanism

ES mechanism – functions:

- free-floating – synchronous backrest and seat tilt,
- backrest tilt synchronised with the seat tilt at rate 2:1,
- backrest tilt angle of 20° synchronised with the seat tilt angle of 11°,
- seat and backrest multi-lock in 5 positions,
- backrest tilt force adjustment with a knob,
- seat depth adjustment 60 mm – as an option (EST),
- Anti-Shock – a feature that controls chair backrest to avoid hitting user's back after releasing the lock,
- smooth height adjustment of the chair with pneumatic gas lift.

2.4. Seat, backrest and headrest

2.4.1. Office swivel chairs

Seat

Structure is made of 8-layer plywood, thickness 11.5 mm covered with cut foam, thickness 40 mm, density 40 kg / m3.

Backrest

Frame is made of glass fiber reinforced polyamide (PA + GF), upholstered in black OP mesh, as standard.

Lumbar support (LU) – made of polyurethane (PU) in black colour, height adjustment in range of 60 mm.

Headrest

Adjustable, fully upholstered (HRUA) – structure is made of 6-layer plywood, thickness 4.5 mm covered with injected foam, both sides upholstered, in the same upholstery type and colour as seat. Headrest supporting element is made of glass fiber reinforced polyamide (PA + GF), in black colour. Height adjustment in range of 60 mm and tilt adjustment.

2.4.2. Conference frame chairs

Seat

Structure is made of 8-layer plywood, thickness 11.5 mm covered with cut foam, thickness 40 mm, density 40 kg / m3.

Backrest

Frame is made of glass fiber reinforced polyamide (PA + GF), upholstered in black OP mesh as standard.

3. Armrests

3.1. Office swivel chairs

Height adjustable armrests – made of glass fiber reinforced polyamide (PA + GF) with black soft polyurethane (PU) pads. Adjustment range of the armrests: height 80 mm.

3-D armrests (R15K-CR i R15K-BL) – made of chromium plated steel or powder-coated in Jet black RAL 9005 and glass fiber reinforced polyamide (PA + GF) with black soft polyurethane (PU) pads. Adjustment range of the armrests: height 80 mm, side movement of the armrests 50 mm, forward/backward movement of the pad 70 mm.

3.2. Conference frame chairs

Fixed armrests – integrated with frame, made of steel tube Ø 25 × 2.5 mm. Armrests pads are made of solid wood painted in black, thickness 22 mm.

4. Packaging

Office swivel chairs – 1 piece per box (chair without headrest unassembled, chair with headrest partially assembled), 10 pieces on pallet.

Conference frame chairs – 1 piece per box (fully assembled), 4 pieces on pallet.

5. Technical regulations, approvals and quality marks for the chairs (for selected product configurations)

Remodex (durability certificate) – approvals compliant with: EN 1335, EN 1022, EN 16139 and EN 1728.